



index

[previous view](#)

F2-71
data sheet

PTFE

F2



EXTRUDED RODS



F2

PTFE

F2-71
data sheet

[previous view](#)



EXTRUDED RODS

Diameter mm	Tolerance mm	Weight kg/m	Lenght mm	Diameter mm	Tolerance mm	Weight kg/m	Lenght mm
4	+0,3 -0	0,03	1000 - 2000 - 3000	35	+1,6 -0	2,20	1000 - 2000 - 3000
5	+0,3 -0	0,05	1000 - 2000 - 3000	38	+1,6 -0	2,61	1000 - 2000 - 3000
6	+0,4 -0	0,07	1000 - 2000 - 3000	40	+1,6 -0	2,90	1000 - 2000 - 3000
7	+0,4 -0	0,09	1000 - 2000 - 3000	42	+2,0 -0	3,08	1000 - 2000 - 3000
8	+0,4 -0	0,12	1000 - 2000 - 3000	45	+2,0 -0	3,64	1000 - 2000 - 3000
9	+0,4 -0	0,15	1000 - 2000 - 3000	50	+2,0 -0	4,47	1000 - 2000 - 3000
10	+0,4 -0	0,18	1000 - 2000 - 3000	55	+2,4 -0	5,40	1000 - 2000 - 3000
11	+0,8 -0	0,23	1000 - 2000 - 3000	60	+2,4 -0	6,38	1000 - 2000 - 3000
12	+0,8 -0	0,26	1000 - 2000 - 3000	65	+2,8 -0	7,48	1000 - 2000 - 3000
13	+0,8 -0	0,32	1000 - 2000 - 3000	70	+2,8 -0	8,70	1000 - 2000 - 3000
14	+0,8 -0	0,36	1000 - 2000 - 3000	75	+3,2 -0	10,12	1000 - 2000 - 3000
15	+0,8 -0	0,41	1000 - 2000 - 3000	80	+3,2 -0	11,48	1000 - 2000 - 3000
16	+0,8 -0	0,46	1000 - 2000 - 3000	85	+3,6 -0	13,20	1000 - 2000 - 3000
17	+0,8 -0	0,52	1000 - 2000 - 3000	90	+3,6 -0	14,51	1000 - 2000 - 3000
18	+0,8 -0	0,60	1000 - 2000 - 3000	100	+4,0 -0	18,30	1000 - 2000 - 3000
19	+0,8 -0	0,65	1000 - 2000 - 3000	110	+5,0 -0	21,78	1000 - 2000 - 3000
20	+0,8 -0	0,72	1000 - 2000 - 3000	120	+5,0 -0	25,55	1000 - 2000 - 3000
22	+1,2 -0	0,89	1000 - 2000 - 3000	130	+5,0 -0	30,97	1000 - 2000
25	+1,2 -0	1,12	1000 - 2000 - 3000	140	+5,0 -0	36,06	1000 - 2000
28	+1,2 -0	1,41	1000 - 2000 - 3000	150	+5,0 -0	41,12	1000 - 2000
30	+1,2 -0	1,62	1000 - 2000 - 3000	160	+6,0 -0	46,65	1000 - 2000
32	+1,6 -0	1,87	1000 - 2000 - 3000				

Note
 Other diameters and lengths available on request.
 Tolerance in lenght: + 2%.
 Disponibili anche precision ground rods
 The indicated weights are only a driving purpose