



index

previous view

F2-73
data sheet

PTFE

F2

MOLTED RODES

Diameter mm	Tolerance mm	Weight Kg/m	Max lenght mm	D x d mm	Tolerance mm	Weight Kg/m	Max lenght mm	D x d mm	Tolerance mm	Weight Kg/m	Max lenght mm
30	+1,2 -0	1,8	200	175	+6,0 -0	57,5	300	340	+8,0 -0	216,6	300
35	+1,6 -0	2,5	200	180	+6,0 -0	60,7	300-1000	345	+8,0 -0	221,3	300
40	+1,6 -0	3,3	200	185	+6,0 -0	64,1	300	350	+8,0 -0	236,0	300
45	+2,0 -0	4,0	300	190	+6,0 -0	69,6	300	365	+8,0 -0	250,6	300
50	+2,0 -0	4,8	300	195	+6,0 -0	70,9	300	380	+10,0 -0	273,2	300
55	+2,4 -0	6,0	300	200	+6,0 -0	73,0	300 - 1000	395	+10,0 -0	291,1	300
60	+2,4 -0	7,2	300	205	+6,0 -0	79,0	300	400	+10,0 -0	307,2	300
65	+2,8 -0	8,3	300	210	+6,0 -0	82,7	300	410	+10,0 -0	312,6	80
70	+2,8 -0	9,5	300	215	+6,0 -0	88,7	300	420	+12,0 -0	339,0	80
75	+3,2 -0	10,8	300	220	+6,0 -0	90,3	300	435	+12,0 -0	357,7	80
80	+3,2 -0	12,3	300	225	+6,0 -0	95,0	300	450	+12,0 -0	390,0	80
85	+3,6 -0	14,0	300	230	+6,0 -0	97,5	300	460	+12,0 -0	397,6	80
90	+3,6 -0	15,2	300	235	+6,0 -0	102,0	300	470	+12,0 -0	416,8	80
95	+4,0 -0	16,9	300	240	+6,0 -0	107,0	300	480	+12,0 -0	434,7	80
100	+4,0 -0	19,2	300	245	+6,0 -0	111,2	300	500	+12,0 -0	465,9	80
105	+5,0 -0	20,7	300	250	+6,0 -0	116,0	300	525	+12,0 -0	520,7	80
110	+5,0 -0	23,0	300	255	+6,0 -0	122,3	300	540	+12,0 -0	549,2	80
115	+5,0 -0	26,0	300	260	+6,0 -0	126,7	300	560	+12,0 -0	576,5	80
120	+5,0 -0	27,7	300	265	+6,0 -0	131,0	300	585	+12,0 -0	645,7	80
125	+5,0 -0	29,7	300	270	+6,0 -0	135,7	300	600	+12,0 -0	679,2	80
130	+5,0 -0	31,5	300	280	+6,0 -0	146,0	300	620	+12,0 -0	725,3	80
135	+5,0 -0	34,3	300	285	+6,0 -0	152,2	300	635	+12,0 -0	760,8	80
140	+5,0 -0	37,3	300	290	+6,0 -0	158,0	300	650	+12,0 -0	797,1	80
145	+5,0 -0	39,6	300	300	+6,0 -0	166,3	300	690	+12,0 -0	898,3	80
150	+5,0 -0	42,3	300	310	+6,0 -0	179,3	300	700	+15,0 -0	924,5	80
155	+6,0 -0	45,3	300	315	+6,0 -0	181,4	300	720	+15,0 -0	976,5	80
160	+6,0 -0	48,7	300	320	+6,0 -0	189,7	300	750	+15,0 -0	1061,3	80
165	+6,0 -0	51,5	300	330	+6,0 -0	212,0	300	770	+15,0 -0	1118,7	80
170	+6,0 -0	55,0	300	335	+8,0 -0	213,0	300				

Note

Tolerance in length: + 15mm -0

The indicated weights are only a driving purpose