



Valvola a 3 vie in esecuzione ASME/ANSI Classe 150 LBS

- Estremità flangiate
- Manovra a leva manuale o con riduttore manuale incluso
- Attuatori disponibili su richiesta per tutti i modelli

Dimensioni conformi a ANSI B16.5 e B16.10

E = spazio richiesto per il rifacimento della boccola misurato come distanza dall'asse

EG = fornite con riduttore manuale incluso

N = numero fori

Due (2) fori sulla parte superiore delle flange sono dotati di filettatura UNC. Vedi colonna fori UNC.

* Le valvole 2 1/2" sono costruite in fusione da 3", ma le flange sono sottoposte a lavorazione fino alle dimensioni 2 1/2"

Sleeved Plug Valves - Multiport ASME/ANSI Class 150 LBS

- Flanged Ends
- Wrench Operated
- Actuators Optional on All Sizes

Dimensions to ANSI B16.5 & B16.10

E = Clearance required for resleeving measured from center line

EG = Enclosed gear operated

N = Number of holes

Two (2) top holes in flanges are tapped with UNC threads. See Hole-UNC column

* 2 1/2" valves are made from 3" casting, but flanges are machined to 2 1/2" dimensions

Dim. Size	L		H		D		K		g		b		f		d		Q		G		Peso Weight		E		N	Foro Hole UNC	
	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	kg	lbs	in	mm	#		
1/2"	4.25	108.00	3.38	86.00	3.50	88.90	2.38	60.5	1.38	35.0	0.37	9.50	0.06	1.60	0.63	16.0	8.00	203.00	8.00	203.00	2.5	6	6.38	162.10	4	-	-
3/4"	4.63	117.50	3.38	86.00	3.88	98.50	2.75	69.9	1.68	42.9	0.37	9.50	0.06	1.60	0.63	16.0	8.00	203.00	8.00	203.00	3.2	7	6.38	162.10	4	-	-
1"	5.00	127.00	4.50	114.00	4.25	108.00	3.13	79.5	2.00	50.8	0.44	11.20	0.06	1.60	0.63	16.0	9.00	229.00	9.00	229.00	5	11	8.50	215.90	4	-	-
1 1/2"	6.50	165.10	5.31	135.00	5.00	127.00	3.88	98.6	2.88	73.2	0.56	14.20	0.06	1.60	0.63	16.0	14.25	362.00	14.25	362.00	8.2	18	10.38	263.70	4	-	-
2"	7.00	177.80	6.25	159.00	6.00	152.40	4.75	120.7	3.63	92.0	0.63	16.00	0.06	1.60	0.75	19.0	16.50	419.00	16.50	419.00	13.6	30	12.25	311.20	4	-	-
*2 1/2"	8.00	203.20	6.56	167.00	7.50	190.50	5.50	139.7	4.13	104.6	0.75	19.00	0.06	1.60	0.75	19.0	16.50	419.00	16.50	419.00	18.2	40	12.63	320.80	4	-	-
3"	8.00	203.20	6.56	167.00	7.50	190.50	6.00	152.4	5.00	127.00	0.75	19.00	0.06	1.60	0.75	19.0	16.50	419.00	16.50	419.00	19.1	42	13.63	346.20	4	-	-
4"	9.00	228.60	7.63	194.00	9.00	228.60	7.50	190.5	6.19	157.2	0.94	23.90	0.06	1.60	0.75	19.0	23.63	600.00	23.63	600.00	32.7	72	16.25	412.80	8	-	-
4" EG	9.00	228.60	9.10	231.00	9.00	228.60	7.50	190.5	6.19	157.2	0.94	23.90	0.06	1.60	0.75	19.0	7.25	184.00	7.25	184.00	41.4	91	17.63	447.80	8	-	-
6" EG	10.50	266.70	10.80	274.00	11.00	279.40	9.50	241.3	8.50	215.9	1.00	25.40	0.06	1.60	0.88	22.4	7.25	184.00	7.25	184.00	70.8	148	21.75	552.50	8	-	-
8" EG	11.50	292.10	12.75	324.00	13.50	342.90	11.75	298.5	10.63	269.8	1.13	28.70	0.06	1.60	0.88	22.4	9.75	248.00	9.75	248.00	117.5	259	26.63	676.40	8	3/4" - 10	-
10" EG	13.00	330.20	14.68	373.00	16.00	406.40	14.25	362.0	12.75	323.9	1.19	30.20	0.06	1.60	1.00	25.4	9.75	248.00	9.75	248.00	181.9	401	31.25	793.80	12	7/8" - 9	-
12" EG	14.00	355.60	16.40	417.00	19.00	482.60	17.00	431.8	15.00	381.0	1.25	31.80	0.06	1.60	1.00	25.4	13.75	349.25	10.00	254.00	-	-	33.75	857.30	12	7/8" - 9	-
14" EG	15.00	381.00	17.40	442.00	21.00	533.40	18.75	476.3	16.25	412.8	1.38	35.10	0.06	1.60	1.12	28.4	13.75	349.25	10.00	254.00	-	-	34.75	882.70	12	1" - 8	-