



Nastri / Tapes

Spessore Thickness mm	Tolleranza Tolerance mm	Peso Weight kg/m ²	Larghezza standard / Standard width (mm)				
			300	600	1000	1200	1500
0,025	+0,01 -0	0,06	✓	✓			
0,05	+0,01 -0	0,12	✓	✓			
0,10	+0,01 -0	0,23	✓	✓	✓	✓	
0,15	+0,02 -0	0,34	✓	✓	✓	✓	
0,20	+0,02 -0	0,46	✓	✓	✓	✓	✓
0,25	+0,02 -0	0,57	✓	✓	✓	✓	✓
0,30	+0,02 -0	0,69	✓	✓	✓	✓	✓
0,35	+0,03 -0	0,81	✓	✓	✓	✓	✓
0,4	+0,03 -0	0,92	✓	✓	✓	✓	✓
0,5	+0,03 -0	1,15	✓	✓	✓	✓	✓
0,6	+0,04 -0	1,38	✓	✓	✓	✓	✓
0,8	+0,04 -0	1,84	✓	✓	✓	✓	✓
1	+0,05 -0	2,30	✓	✓	✓	✓	✓
1,5	+0,10 -0	3,45	✓	✓	✓	✓	✓
2	+0,20 -0	4,60	✓	✓	✓	✓	✓
2,5	+0,30 -0	5,75	✓	✓	✓	✓	✓
3	+0,30 -0	6,90	✓	✓	✓	✓	✓
4	+0,35 -0	9,20	✓	✓	✓	✓	✓
5	+0,40 -0	11,50	✓	✓	✓	✓	✓
6	+0,40 -0	13,80	✓	✓	✓	✓	

Note

Dimensioni e spessori diversi su richiesta.
I nastri possono essere forniti con una o ambedue le superfici trattate chimicamente in modo che il PTFE possa essere incollato.
Tolerances on width: +3%.
Weights stated are for guide purposes only

Note

Other sizes and thicknesses available on request.
Tapes are also available with one or both sides chemically treated, in order to apply the PTFE tape on other materials.
Tolerances on width: +3%.
Weights stated are for guide purposes only