

F2

PTFE

F2-82

data sheet

[vista precedente](#)



[indice](#)

MANICOTTI

| Diametro esterno mm | Diametro interno mm | Diametro esterno mm | Diametro interno mm | Diametro esterno mm | Diametro interno mm |
|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| 1520 | 1420 | 1710 | 1570 | 1910 | 1760 |
| | 1470 | | 1610 | | 1800 |
| 1570 | 1520 | | 1660 | | 1850 |
| 1620 | 1470 | | 1810 | 1660 | 2010 |
| | 1520 | 1710 | | 1900 | |
| | 1570 | 1770 | | 1950 | |

Massima lunghezza 100 mm

MANICOTTI ISOSTATICI

| Diametro esterno mm | Diametro interno mm | Diametro esterno mm | Diametro interno mm | Diametro esterno mm | Diametro interno mm |
|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| 85 | 65 | 93 | 78 | 100 | 90 |
| | 68 | | 80 | | 103 |
| | 70 | | 83 | 85 | |
| | 73 | | 85 | 88 | |
| | 75 | | 95 | 75 | 90 |
| 88 | 78 | 98 | 78 | 105 | 93 |
| | 68 | | 80 | | 95 |
| | 70 | | 83 | | 88 |
| | 73 | | 85 | | 90 |
| | 75 | | 88 | | 93 |
| | 78 | | 80 | | 95 |
| 90 | 70 | 100 | 83 | 108 | 98 |
| | 73 | | 85 | | 93 |
| | 75 | | 88 | | 95 |
| | 78 | | 90 | | 98 |
| | 80 | | 80 | | 100 |
| | 83 | | 83 | | 95 |
| 93 | 73 | 100 | 85 | 110 | 98 |
| | 75 | | 88 | | 100 |

Tolleranze (sul diametro esterno D)

- Diametro 85 ÷ 100mm: +4,0 -0 mm
- Diametro 103 ÷ 110mm: +5,0 -0 mm

Tolleranza sul diametro interno d: -6% +0
Lunghezza 600 mm